PHILIP MORRIS

MATERIAL SPECIFICATION



12-553-C

DATE:

5/10/94

SUPERSEDES:

D/M CDDE:

10/04/93

DESCRIPTION:

64MM X 3500M WHITE TGL

KC 265M2

PERFORATED TIPPING

CURRENT

BRANDS:

L & M MENTHOL LONGS - GCC TAR/NICOTINE

05180(GCC)

UNPERFORATED TIPPING

PAPER DESCRIPTION:

64MM X 3500M WHITE TGL KC 265M2 11-549-A

TYPE OF PERFORATION:

LASER PERF.

PERFORATION R.T.D.:

3.00 cm + / - 0.30 cm

TESTED AT:

17.5CC/SEC. ON MODIFIED PM HEAD

NUMBER OF ROWS:

2

HOLES/INCH/ROW:

35 TO 45

BAND LOCATIONS:

A. DISTANCE BETWEEN PERFORATIONS:

24.00mm +/- 1.00mm

B. PERFORATED BAND WIDTH:

1.50 mm + / - 0.50 mm

C. EDGE OF PERF. BAND TO EDGE OF TIPPING PAPER:

 $18.50 \, \text{mm} + / - 1.00 \, \text{mm}$

REASON FOR CHANGE:

PERFORATION RTD/PM MAT'L CODE CHGD FROM 2.5CM +/-

.30CM (12-553-B) TO 3.0CM +/-.30CM (12-553-C).

CC: L/V QA

E. W. WESTON. M/C, EW-2

PREPARED BY: ALLYSON M. MILBURN (05/09/94) APPROVED BY:

MANUFACTURING SPECIFICATIONS

SAP Bom 98/4.29.95

Source: https://www.industrydocuments.ucsf.edu/docs/pswy0004